

## A TWO-PHASE SOLID/FLUID MODEL FOR DENSE GRANULAR FLOWS INCLUDING DILATANCY EFFECTS

A. Mangeney<sup>1,2</sup>, F. Bouchut<sup>3</sup>, E. D. Fernandez-Nieto<sup>4</sup>, E. Koné<sup>1</sup>, G. Narbona-Reina<sup>4</sup>

<sup>1</sup>*Institut de Physique du Globe & Université Paris-Diderot, Sorbonne Paris Cité, France*

<sup>2</sup>*ANGE Team, CEREMA, Inria, Lab. J.-L. Lions, CNRS, France*

<sup>3</sup>*CNRS & Université Paris-Est, France*

<sup>4</sup>*University of Sevilla, Applied Mathematics, Sevilla, Spain*

*Key words* debris flows, two-phase granular flows, dilatancy

Describing grain/fluid interaction in debris flows models is still an open and challenging issue with key impact on hazard assessment [1, 2]. We present here a two-phase two-thin-layer model for fluidized debris flows that takes into account dilatancy effects. It describes the velocity of both the solid and the fluid phases, the compression/dilatation of the granular media and its interaction with the pore fluid pressure [3].

The model is derived from a 3D two-phase model proposed by Jackson [4] based on the 4 equations of mass and momentum conservation within the two phases. This system has 5 unknowns: the solid and fluid velocities, the solid and fluid pressures and the solid volume fraction. As a result, an additional equation inside the mixture is necessary to close the system. Surprisingly, this issue is inadequately accounted for in the models that have been developed on the basis of the work of Jackson [5]. In particular, Pitman and Le [6] replaced this closure simply by imposing an extra boundary condition at the surface of the flow. When making a shallow expansion, this condition can be considered as a closure condition. However, the corresponding model cannot account for a dissipative energy balance.

We propose here an approach to correctly deal with the thermodynamics of the model of Jackson by closing the mixture equations by a weak compressibility relation following Roux and Radjai [7]. This relation implies that the occurrence of dilation or contraction of the granular material in the model depends on whether the solid volume fraction is respectively higher or lower than a critical value. When dilation occurs, the fluid is sucked into the granular material, the pore pressure decreases and the friction force on the granular phase increases. On the contrary, in the case of contraction, the fluid is expelled from the mixture, the pore pressure increases and the friction force diminishes. To account for this transfer of fluid into and out of the mixture, a two-layer model is proposed with a fluid layer on top of the two-phase mixture layer. Mass and momentum conservation are satisfied for the two phases, and mass and momentum are transferred between the two layers. A thin-layer approximation is used to derive average equations. Special attention is paid to the drag friction terms that are responsible for the transfer of momentum between the two phases and for the appearance of an excess pore pressure with respect to the hydrostatic pressure.

We present several numerical tests of two-phase granular flows over sloping topography that are compared to the results of the model proposed by [6]. In particular, we quantify the role of the fluid and compression/dilatation processes on granular flow velocity field and runout distance.

### References

- [1] R.M. Iverson, M. Logan, R.G. LaHusen, M. Berti, *The perfect debris flow? Aggregated results from 28 large-scale experiments*, J. Geophys. Res. **115**, F03005 (2010).
- [2] R. Delannay, A. Valance, A. Mangeney, O. Roche, P. Richard, *Granular and particle-laden flows: from laboratory experiments to field observations*, J. Phys. D: Appl. Phys., submitted (2016).
- [3] F. Bouchut, E. D. Fernández-Nieto, A. Mangeney, G. Narbona-Reina, *A two-phase two-layer model for fluidized granular flows with dilatancy effects*, J. Fluid Mech., submitted (2016).
- [4] R. Jackson, *The Dynamics of Fluidized Particles*, Cambridge Monographs on Mechanics (2000).
- [5] F. Bouchut, E.D. Fernández-Nieto, A. Mangeney, G. Narbona-Reina, *A two-phase shallow debris flow model with energy balance*, ESAIM: Math. Modelling Num. Anal., **49**, 101-140 (2015).
- [6] E.B. Pitman, L. Le, *A two-fluid model for avalanche and debris flows*, Phil.Trans. R. Soc. A, **363**, 1573-1601 (2005).
- [7] S. Roux, F. Radjai, *Texture-dependent rigid plastic behaviour*, Proceedings: Physics of Dry Granular Media, September 1997. (eds. H. J. Herrmann et al.). Kluwer. Cargèse, France, 305-311 (1998).